

LEVELUK SD501/JR11/JR1V DEEP CLEANING MANUAL



1) Turn off the machine



2) Remove cover



3) Remove the filter



4) Take out CPU-N



5) Place the CPU in the machine where the filter was.



6) Prepare 1 container



7) Prepare 1 glass citric acid (300gram)



8) Prepare 1 glass hot water



9) Pour 1 glass citric acid onto the container



10) Pour 1 glass hot water onto the container



11) Dissolve the solution



12) Add 1 liter tap water onto the container.



13) Place pump and acidic hose (grey hose) into the container.



14) Power on the pump.

Let pump run
30 minutes
to 1 hour

15) Let pump running for 30 minutes to 1 hour



16) Power off the pump.



17) Disconnect white hose from pump hose.



18) Connect white hose to tap water. Then rinse the machine by running water for 5 minutes



19) Remove the CPU



20) Put your filter back in (When storing your CPU don't store it wet with the lid on, allow it to completely dry.)



21) Put your cover back in.

Finish

NOTES:

Even when you do e-cleanings regularly, you will still need to have a deep cleaning done at least once a year. This will ensure maximum effectiveness and yield the best results for your Kangen Water®.

The optimum pump pressure range between 16 ~ 21 liter/minutes.

ENAGIC (MALAYSIA) SDN BHD
Company No. 201101042983

Direct Sales License No.: AJL931978

Unit 25&27-6,6F The Boulevard, Mid Valley City,
Lingkaran Syed Putra, 59200 Kuala Lumpur

Tel: 603-2282 2332 Fax: 603-2282 2335 www.enaqic-mv.com